

**PRODUCT  
DATA SHEET:  
HOLLOW  
METAL  
DOORS**

**SPECIFICATIONS**

Thickness:	1 3/4"
Actual Door Size:	Door undersized from nominal by 1/4" in width and 7/8" in height. Standard undercut is 3/4".
Hinge Reinforcement:	7-gauge, non-beveled with 1/4" hinge backset.
Lock Reinforcement:	14-gauge reinforcement for mortise lock and cylindrical locks in accordance with ANSI A115 Standards.
Edge Seams:	Continuously welded vertical lock and hinge edges for superior strength
Top Channel:	Flush, 16-gauge channel, welded at a maximum 2 1/2" on center
Bottom Channel:	Inverted 16-gauge channel, welded at a maximum 2 1/2" on center.
Core:	Polystyrene insulated
Face Skins:	18-gauge A40 Galvannealed Steel available in flush, 6-panel and 2-panel designs
Closer	12-gauge standard. (18" x 6")
Reinforcement:	
Size Availability:	Minimum 2068, Maximum 4080
SDI 100 Level/Model:	Level 2 Model 1 or 2 (Heavy Duty, minimum 18-gauge
Handing Design:	Non-handed
Fire Ratings:	Fire rated up to 3 hour in accordance with UL 10C and UL 10B standards
Paint Finish:	Doors will be cleaned, treated and coated with a baked on alkyd enamel rust inhibitive primer in accordance with ANSI A250.10-2025.

